



Product Catalogue 2024

SECTION 2 | BALUSTRADE AND POOL

Product	Page
Channel Systems	2 - 11
- SMART LOCK Channel	4 - 7
- VISTA Channel	8 - 9
Stand-off Disc Systems	10 - 23
- SD50 Discs	12 - 15
- SD75 Discs	16 - 17
- SD100 Discs	18 - 19
- PF150 Discs	20 - 21
- PRADIS Clamp	22 - 23
Semi-Frameless Posts	24 - 25
Mini Posts & Spigots	26 - 33
- SSP15/10 Oval Base Fixed Strut Posts	29
- SP13 Face/Side Fixed Strut Posts	30
- SP14 Centrally Fixed Strut Posts	31
- PR160 Round Base Fix Spigot	32
- PS175 Square Base Fix Spigot	33
Gate Hinges, Latches & Pivots	34 - 39
Handrail Systems & Clamps	40 - 45
Opus Hardware Service Offering - (Freight + Powdercoating)	46 - 47



SYSTEM	MAX WIND LOAD (Subject to glass type & xing method)	OCCUPANCY TYPE/S	GLASS CAPACITIES	SUITABLE SUBSTRATE
SMART LOCK (Top & Side Fix)	Extra High	A, B, E, C1/C2, C3, D	12mm to 21.52 mm	Concrete, Timber, Steel
VISTA (Side Fix)	Extra High	A, B, E & C3	12mm - 17.5mm	Concrete, Timber, Steel

PRODUCT OVERVIEW | CHANNEL SYSTEMS



SMART LOCK | Top/Side Fixed Channel

The Smart Lock System was developed for cantilevered structural balustrades to cope with the transition from monolithic Toughened Safety Glass (TSG) to Toughened Laminated Safety Glass (TLSG). The unique design uses a special high strength hollow-core aluminium extrusion and special (single side adjustment) glass clamp kits that secure and locate the glass into the aluminium section.

PAGES: 6 - 9



CLEARVISTA | Side Fixed Channel

The Vista Channel is an ideal system for Deck Balustrades. Providing a slim, minimalistic look while delivering unobscured views, superior strength, durability and paramount safety. The Vista System has been crafted using high strength extruded aluminium and can be fin shed in a powder coat colour of your choice.

PAGES: 18 - 19



SMART LOCK 3.0 METRE KITS

PRODUCT & DESCRIPTION	FINISH	GLASS SIZE	CODE	3.0M PRICE
		12mm	SL120B12	
SL120B Base Fix System	Satin Stainless Brushed	15mm	SL120B15	
Complete with cladding cover, gaskets and glass clamps. (3.0 metre kit)		19mm	SL120B19	
		13.5mm	SL120B13	
		17.5mm	SL120B17	
		21.5mm	SL120B21	
		12mm	SL120BK12	
	Black (Brushed ANO)	15mm	SL120BK15	
		19mm	SL120BK19	
		13.5mm	SL120BK13	
		17.5mm	SL120BK17	
		21.5mm	SL120BK21	
SL120S Side/Face Fix System		12mm	SL120S12	
Complete with seal strip, gaskets,	Satin Stainless Brushed	15mm	SL120S15	
side cladding cover and glass clamps. (3.0 metre kit)		19mm	SL120S19	
		13.5mm	SL120S13	
	2	17.5mm	SL120S17	
		21.5mm	SL120S21	
		12mm	SL120SBK12	
, 6	Black (Brushed ANO)	15mm	SL120SBK15	
A. C.		19mm	SL120SBK19	
		13.5mm	SL120SBK13	
		17.5mm	SL120SBK17	
		21.5mm	SL120SBK21	

^{*} Powdercoat or Anodising P.O.A.





^{*} Additional Fixing Kits on page 9.

^{*} No Glass Cutouts Required.

^{*} Pricing is in 3 metre kits

SMART LOCK COMPONENTS

PRODUCT	DESCRIPTION	FINISH	CODE	3.0M PRICE		
	Base Channel Only (Drilled) 3.0mtr	MILL	SLMC			
	Side Cladding Only 3.0M	Satin Stainless (Brushed ANO)	SLSC-SS			
		Black (Brushed ANO)	SLSC-BK			
	Top Seal Strip Only	Satin Stainless (Brushed ANO)	SLTS-SS			
	*Doesn't include bulb seal, please refer to Bulb Seal Gasket section for respective glass thicknesses. 3.0M	Black (Brushed ANO)	SLTS-BK			
		Satin Stainless (Brushed ANO)	SLBC-SS			
	Bottom Cladding Only 3.0M	Black (Brushed ANO)	SLBC-BK			
*Powdercoat or Anodising P.O.A (*Pricing per le						

PRODUCT	DESCRIPTION	GLASS SIZE	CODE	PRICE
Glass Clamp Kits Only *each kit contains 10 clamps		to suit 12mm glass	SLC12	
	to suit 15mm glass	SLC15		
		to suit 19mm glass	SLC19	

PRODUCT	DESCRIPTION		SIZE	FINISH	CODE	PRICE
		Base Fix	suit SL120B	Satin	SLECB-SS	
	End Caps	Face Fix	suit SL120S	Satin	SLECS-SS	
	*price per cap	Base Fix	suit SL120B	Black	SLECB-BK	
		Face Fix	suit SL120S	Black	SLECS-BK	

SMART LOCK COMPONENTS & FIXING KITS

PRODUCT	DESCRIPTION	SIZE	CODE	PRICE
3	Quick Lock Ratchet Spanner For fittment and adjustmen		SLSS	

PRODUCT	DESCRIPTION		CODE	PRICE	
	Fixing Kits Side/Fac		Concrete	SLCFIX1	
		Paga/Tap Fix	Steel	SLSFIX1	
		base/ Top Fix	Timber (Through Bolt)	SLTBFIX1	
2000			Timber (Lag Screw)	SLLSFIX1	
			Concrete	SLCFIX2	
		0:4-/5 5:	Steel	SLSFIX2	
		Side/Face Fix	Timber (Through Bolt)	SLTBFIX2	
		-	Timber (Lag Screw)	SLLSFIX2	

^{*}EPDM Washers not included in Kits. Fixing Kits sold per mounting hole set.

^{*}Additional Adhesives, Sealants may be required,

^{*}Fxing kits include stainless fix ures only.



VISTA KITS & COMPONENTS

PRODUCT	DESCRIPTION	LENGTH	CODE	PRICE
	Vista System Kits	Full length 4.8m	OBFC-48M	
	(Mill Finish)	Per mtr	OBFC	

^{*}Kits come complete with Channel, Front & Back covers, Clamping plate, Grub screws & Plastic packers.

^{*}No Glass Cutouts Required

PRODUCT	DESCRIPTION	LENGTH	CODE	PRICE
	Channel Only	4.8m	OBFCB48	
	(Drilled)	2.4m	OBFCB24	
	Innor Clamp Only	4.8m	OBFCFI48	
	Inner Clamp Only	2.4m	OBFCIC24	
	Front Cover Only (Mill)	5m	OBFCFC48	
		2.5m	OBFCFC24	
	Back Cover Only (Mill)	5.2m	OBFCBC48	
		2.6m	OBFCBC24	
	End Cap		OBFCEC	
PRODUCT	DESCRIPTION	TYPE	CODE	PRICE
0		Concrete	OFIX7	
	Finis a Vita	Steel	OFIX	
	Fixing Kits	Timber (Through Bolt)	OFIX6	
		Timber (Lag Screw)	OFIX8	

^{*}Suits 12-17.5mm Glass (May require Specific Design

^{*}Powdercoat or Anodising P.O.A



SYSTEM	MAX WIND LOAD (Subject to glass type & xing method)	OCCUPANCY TYPE/S	GLASS CAPACITIES	SUITABLE SUBSTRATE
SD50 (50mm Double Disc System)	Extra High	A, B, E & C3	12mm - 17.5mm	Concrete, Timber, Steel
SD75 (75mm Single Disc System)	Extra High	A, B, E & C3	12mm - 17.5mm	Concrete, Steel
SD100 (100mm Single Disc System)	Very High	A, B, E & C3	12mm - 17.5mm	Concrete, Steel
PF150 (Point Fix Plate System)	Very High	A, B, E & C3	12mm - 17.5mm	Concrete, Timber, Steel
PRADIS (Standoff radis Clamp System)	Extra High	A, B, E, C1/C2, C3, C5, D & F	12mm to 21.5mm	Concrete, Timber, Steel

PRODUCT OVERVIEW | STANDOFF FITTINGS



SD50 | 50mm DoubleDisc System

The DoubleDisc SD50 system is a 50mm diameter traditional stainless steel anchor xing o ering, ideal for those seeking a more industrial frameless glass balustrade aesthetic. The standoff ody sets the glass panels out from the deck to assist with water draining and cleaning. The system is ideal for external/internal balconies, stairs and landings. It can be xed directly to either timber, steel or concrete surfaces and is nished with an interlinking top rail (where required) in a choice of stainless steel or powder coat colours to suit. The nish options are mirror polished stainless steel with a hidden xing detail or satin stainless steel with a visible xing detail. Adjustable options are also available.

PAGES: 24 - 27



SD75 | 75mm Single Disc System

The SingleDisc SD75 was born from testing and modelling balustrade xings to determine the optimum economical ting for clamp xing balustrades. The outer disc was pro led to give an attractive appearance and the single xing point means it can be located on the edge of narrow concrete slabs or steel pro les.



PAGES: 28 - 29

SD100 | 100mm Single Disc System

The SingleDisc SD100 was designed to provide a more solid aesthetic look to single point clamping, as an alternative option to DoubleDisc, SD50 or continuous plate systems. The outer and inner discs are simple circular prolles and the single oxing point means it can be located on the edge of narrow concrete slabs or steel prolles.



PAGES: 30 - 31

PF150 | Point Fix Plate System

Designed in response to demands for maximum visibility, the PlateFix PF150 Frameless Glass Balustrade presents minimal xings and clearer views beyond the glass panels. The PlateFix PF150 is an marine grade stainless steel clamp that xes 12mm/17.52mm thick toughened glass panels to the external edge of balconies and stairs - as well as for internal stairs and landings. The PlateFix PF150 has a wide body which sets the glass out from the deck 20mm, assisting with water drainage and cleaning, but xing centres are up to 50% narrower than our traditional DoubleDisc Anchors - providing a comparatively less visual and far more linear xing detail.

PAGES: 32 - 33



PRADIS | Standoff Pradis Clamp System

Pradis Balustrade showcases the latest in face xing technology allowing the Pradis clamps to be located up to 800mm from one another for modern simplicity. Pradis is stronger than other conventional systems; anchors, single disc etc. Quick to install and easy to adjust. The Pradis can be xed to a 150mm tall substrate.

PAGES: 34 - 35



SD50 DISC ASSEMBLIES

PRODUCT	DESCRIPTION	STANDOFF SIZE	FINISH	CODE	PRICE
	SD50 Screw Head 50mm diameter assembly with	30mm (other sizes	Polished Stainless	SD5030-SH-PS	
10	stand-o , and fl t edge screw head.	available)	Satin Stainless	SD5030-SH-SS	
	SD50 Flat Head 50mm diameter assembly	20	Polished Stainless	SD5030-FH-PS	
	with stand-o , and fl t edge concealed stepped head.	30mm (other sizes available)	Satin Stainless	SD5030-FH-SS	
	0050 D 111	30mm (other sizes	Polished Stainless	SD5030-BH-PS	
The second second	SD50 Beveled Head 50mm diameter assembly with stand-o, and beveled fl t	available)	Satin Stainless	SD5030-BH-SS	
	edge concealed head.		Black (PVD)	SD5030-BH-BK	
	SSD50 Square Anchor	0.5	Polished Stainless	SSD5025-FH-PS	
	50mm Square assembly with stand-o , and fl t edge concealed head.	25mm	Satin Stainless	SSD5025-FH-SS	
	SD50/A Adjustable Anchor	Adjustable	Polished Stainless	ASD5030-SH-PS	
To	50mm diameter assembly with an adjustable stand-o , and fl t edge screw head.	(40-50mm)	Satin Stainless	ASD5030-SH-SS	
	Glass to Cleat Anchor 50mm diameter with round edge head and stando . Glass to cleat fixing. o suit 10, 12 and 15mm toughened glass.	6mm	Satin Stainless	CA50-SS	
	Square Cover Kit	30mm	Polished Stainless	SD50SCK-PS	
	To Convert SD50 Fittings Round Fixings to Square Sets.	30mm	Satin Stainless	SD50SCK-SS	

^{*}Fixings ordered separately, see M10 Rod and Lag Screw options (page 29)



^{*}Options for up to 12 - 17.5mm glass.

^{*}SPECIFY GLASS THICKNESS ON ORDER.

50MM DISC COMPONENTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	50mm CSK Head Only	Polished Stainless	SDSH-PS	
	M10	Satin Stainless	SDSH-SS	
8	50mm Flat Head Only	Polished Stainless	SDFH-PS	
	50mm Dia x 10mm M10	Satin Stainless	SDFH-SS	
	50mm	Polished Stainless	SDBH-PS	
	Beveled Head Only м10	Satin Stainless	SDBH-SS	
		BODY WIDTH	CODE	PRICE
	50mm Threaded Body	6mm	SDB6-SS	
		20mm	SDB20-SS	
	Only	25mm	SDB25-SS	
	M10	30mm	SDB30-SS	
		40mm	SDB40-SS	
		50mm	SDB50-SS	
		6mm	SDS6-SS	
	50mm Spacer Only	20mm	SDS20-SS	
	10.5mm Through Hole	25mm	SDS25-SS	
		30mm	SDS30-SS	
0	50mm Weatherboard Shim 8 degree angle, 12mm tapered to 5mm, 10.5mm dia. through hole, SS.	12mm > 5mm	SP505WBSS	

50MM DISC FIXINGS

PRODUCT	DESCRIPTION	M SIZE	LENGTH	CODE	PRICE
		•	50mm	M10-R50	
	Stainless Steel Rods	100mm M10 115mm	100mm	M10-R100	
			M10-R115		
			140mm	M10-R140	
	SS Lag Screw	M10	100mm	LS10100	
	(External Application)	WIIO	120mm	LS10120	
	Zinc Plated		70mm	LS100702L	
	Lag Screw (Internal Application)	M10	100mm	LS101002L	
			120mm	LS101202L	
PRODUCT	DESCRIPTION	SIZE		CODE	PRICE
	Hex Nut	M10		M10-HN	
	Dome Nut	M10		M10-DN	
	Nylon Bush	19.5mm Dia		NB-20	
	to suit M10 Rod			110 20	
	Black Fibre Gasket				
	0.8mm Thick, for Exterior and Interior Applications		50mm Dia	FG-50	
	Opaque LDPE Gasket 0.8mm Thick, for Interior Applications	50mm Dia		LG-50	
		M10 x 30m	m dia washers 2.5mm	M10-30	
	Washers	50 x 50 x 3 Flat Square Washer SS		M10-SQ	
	Spring Washer	M10 Spring	Washer SS	M10-5HR	



SD75 DISC ASSEMBLIES

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	SD75 Screw Head			
	75mm diameter assembly with 30mm stand-o , and beveled edge screw head.	Satin Stainless	SD75	
	Fitting suitable for single lineFixings at 400mmm max centresGlass hole 25mm			
	Square Cover Kit	Polished Stainless	SD75SCK-PS	
	To Convert SD75 to square fitting 30mm Stando	Satin Stainless	SD75SCK-SS	

^{*}Fixings ordered separately, see M12 Rod options below *Options for up to 12 - 17.5mm glass.

*SPECIFY GLASS THICKNESS ON ORDER.

PRODUCT	DESCRIPTION	M SIZE	LENGTH	CODE	PRICE
	Stainless Steel Rods		60mm	M12-R60	
1.		M12	120mm	M12-R120	
			150mm	M12-R150	
	M12 Hex Nut			M12-HN	
	M12 Dome Nut			M12-DN	
	Black Fibre Gasket 0.8mm Thick, for Exterior and In 75mm Dia	FG-75			
	Opaque LDPE Gasket 0.8mm Thick, for Interior Applications 75mm Dia			LG-75	
•	Washers	M12 x 24mm dia	washers 2.5mm SS	FW1224	
e75	Tapered shim	Tapered shim for MB75 fixing.	1-2m	TS75-1-2	
	Black nylon material.	Tapered shim for MB75 fixing.	1-3m	TS75-1-3	



PRODUCT OVERVIEW | SD100 DISCS 100MM BUTTON FITTINGS SD100 DISCS



SD100 DISC ASSEMBLIES

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	SD100 Screw Head			
(=)	100mm diameter assembly with 30mm stand- o , and beveled edge screw head.		SD100	
	Compliant to NZS1170 for use in domestic and commercial installations	Satin Stainless		
	Fitting suitable for single lineFixings at 400mmm max centresGlass hole 25mm			
	*SD100 is made to order.			

^{*}Fixings ordered separately, see M12 Rod and Lag Screw options below *Options for up to 12 - 17.5mm glass.

*SPECIFY GLASS THICKNESS ON ORDER.

PRODUCT	DESCRIPTION	M SIZE	LENGTH	CODE	PRICE
	Stainless Steel Rods		60mm	M12-R60	
		M12	120mm	M12-R120	
			150mm	M12-R150	
	M12 Hex Nut			M12-HN	
	M12 Dome Nut			M12-DN	
	Black Fibre Gasket 0.8mm Thick, for Exterior and Interior Applications 100mm Dia				
Opaque LDPE Gasket 0.8mm Thick, for Interior Applications 100mm Dia			LG-100		
•	Washers M12 x 24mm dia washers 2.5mm SS			FW1224	





PF150 PLATEFIX ASSEMBLIES

PRODUCT	DESCRIPTION	CODE	PRICE
	PF150 Plate Fix Fitting.		
	Single or Double point fixing		
	316SSS Finish.		
	20mm stand off space , 6mm outer plate.	PF150	
6	150mm long with 50mm radius ends.		
	Compliant to AS/NZ1170 for use in both domestic and commercial balustrades and pool fences.		

 $^{^*\}mbox{Fixings}$ ordered separately, see M12 Rod and Lag Screw options below $^*\mbox{Options}$ for up to 12 - 17.5mm glass.

*SPECIFY GLASS THICKNESS ON ORDER.

PRODUCT	DESCRIPTION	CODE	PRICE
	Wood fix M10 x 120mm CSK Socket screw, 50mm diameter Washer & Hex Nut - 316SSS (Double point fix X 2 fixin	CBW-120	
00	Wood fix M12 x 130mm CSK Socket screw, 50mm diameter Washer & Hex Nut - 316SSS (Single point fix X 1 fixin	CBW-130	
	Hilti 10mm Masonry Sleeve (Double point fix X 2 fixing	MF110	
1	Hilti 12mm Masonry Sleeve (Single point fix X 1 fixin	MF125	
•	Metal Fix 10 x 50mm CSK Socket screw, fl t washer & Hex Nut 316SSS (Double point fix X 2 fixing	SF50-10	
	Metal Fix 12 x 50mm CSK Socket screw, fl t washer & Hex Nut 316SSS (Single point fix X 1 fixin	SF50-12	





PRODUCT DESCRIPTION CODE PRICE

Pradis Face Mounted Clamp


PRADIS Anodised Aluminium Clamps can be fi ed to the following diffe ent substrate types; Concrete, Steel, Timber. Suitable for glass thickness from 12mm to 22.38mm (can be adapted to take other glass thicknesses - upon request)




Clama with Fiving Vit	Satin ANO	EZ1-SA
Clamp with Fixing Kit	Black	EZ1-BLK
Kit for bolt through xings.	Satin ANO	EZ1BT-SA
M12 x 170mm threaded stud 50 x 50mm square washer, M12 nut.	Black	EZ1BT-BLK
Kit for Steel Substrates M12 x 100mm threaded stud, M12 Nut	Satin ANO	EZ1S-SA
	Black	EZ1S-BLK
Kit for lag screw xings for exposed Timber substrates.	Satin ANO	EZ1LE-SA
M12 x 200mm lag screw	Black	EZ1LE-BLK
Kit for lag screw xings for concealed Timber substrates.	Satin ANO	EZ1LC-SA
M12 x 160mm lag screw, EPDM washer	Black	EZ1LC-BLK
Kit for Concrete substrates	Satin ANO	EZ1C-SA
M12 x 170mm threaded stud	Black	EZ1C-BLK

^{*}SPECIFY GLASS THICKNESS ON ORDER.

^{*}SPACINGS VARY DEPENDING ON FIXINGS AND SUBSTRATE.







SEMI-FRAMELESS POSTS

PRODUCT DESCRIPTION



Semi-Frameless Balustrade Posts

The Resolute & Milano Balustrade is a frameless full height post system where the top and bottom edges of the glass are exposed. This system can be used as a pool fence, balustrade or as a wind break.

Unlike other systems the posts can be fi ed up to 1650mm apart and with 500mm overhangs allows for a panel width of 2650mm overall, which reduces the amount posts required across the deck (Balustrade post locations are based on the wind zone). Based on design loads from AS/NZS 1170.1 and a max uls wind pressure of 2.13kPa (Extra high wind zone).

Rated for occupancy A, B, E, C1, C2, C3, D and C5. Suited for 8-17.5mm glass.

Fixed at 1650mm centres Max, Maximum height 2000mm, Maximum glass overhang 500mm (each side).


*Posts are all P.O.A - Please contact the team for further information & pricing.

PRODUCT	DESCRIPTION	ON	FIXING TYPE	CODE	PRICE
	Floor Mount		Concrete	OB100-C	
	Includes 1x Post and fixing kit specifie		Timber/Steel	OB100-T	
	Face Fixed		Concrete	OB101-C	
- 1		: <i>t</i> :	Bolt Through	OB101-T	
- 1	Includes 1x Post and fixing kit s	респе	Steel	OB101-S	
	Face Fixed		Concrete	OB101C-C	
	*With Concealed Fixings Includes 1x Post and fixing kit specifie		Steel	OB101C-S	
SYSTEM	MAX WIND LOAD (Subject to glass type & xing method)	OCCUPANCY TYPE/S	GLASS CAPACITIES	MAXIMUM HEIGHTS	SUITABLE SUBSTRATE
RESOLUTE/ MILANO	Extra High	A, B, E, C1, C2, C3, C5, D	8mm - 17.5mm	2000mm above top xing	Concrete, Timber, Steel



SYSTEM	MAX WIND LOAD (Subject to glass type & xing method)	OCCUPANCY TYPE/S	GLASS CAPACITIES	SUITABLE SUBSTRATE	
SP15	Evtro High	A, B, E & C3	- 12mm - 17.5mm	Onnersta Timber Otani	
3713	Extra High	Pool Fencing	12111111 - 17.5111111	Concrete, Timber, Steel	
CD10	Medium	A, B, E & C3	- 10mm - 13.5mm	Congrete Timber Steel	
SP10	Medium	Pool Fencing	iomm - is.smm	Concrete, Timber, Steel	
CD12	France I limb	A, B, E & C3	- 12mm - 17.5mm	Concrete, Timber, Steel	
SP13	Extra High	Pool Fencing	12mm - 17.5mm	Concrete, Timber, Steel	
CD14	France I II ala	A, B, E & C3	- 12mm - 17.5mm	Congrete Timber Steel	
SP14	Extra High	Pool Fencing	12mm - 17.5mm	Concrete, Timber, Steel	
D017F	Madiana	A & C3	10	On and Timber Charles	
PS175	Medium	Pool Fencing	10mm to 12mm	Concrete, Timber, Steel	
DD1/0	11:	A & C3	10	On and Timber Charles	
PR160	High	Pool Fencing	10mm to 12mm	Concrete, Timber, Steel	

PRODUCT OVERVIEW | SPIGOTS & STRUT POSTS



SP15/10 | Base Fix

The Oval Base x Strut Posts SP15 & SP10 are a popular choice when it comes to unmatched quality and ease of use. The stunning strut design creates an architectural statement in itself, available in Polished, Satin or Brushed Black. These can be used with 10mm up to 17.52mm Glass.



PAGE: 43



SP13 | Face/Side Fixed

The Face/Side x Strut Post SP13 is a new product complimenting the base xed posts to allow side xing applications with larger Glass spans and sizes. These are a popular choice when it comes to unmatched quality and ease of use. The stunning strut design creates an architectural statement in itself, available in Polished, Satin or Black. These can be used with 12mm up to 17.52mm Glass.



PAGE: 44





The Centrally xed Strut Post SP14 is a new product complimenting the base and side xed posts to provide a seamless and stunning fin shed application with all xings concealed within the core. These are a popular choice when it comes to unmatched quality and ease of use. The stunning strut design creates an architectural statement in itself, available in Polished, Satin or Brushed Black. These can be used with 12mm up to 17.52mm Glass.



PAGE: 45





Economical Round Spigot base xed option for pool fences and balustrades. The PR160 Spigot is great option for professionals who want to be able to use an economical spigot for both Pool and Balustrade without the need to compromise with the product tested to perform.

- 10-12mm Glass
- Adjustable base plate
- Compatible with MOOD LED System





PS175 | Square Base Fix Spigot



Economical Square Spigot base xed option for pool fences and balustrades. Like the PR160, The PS175 Spigot is great option for professionals who want to be able to use an economical spigot for both Pool and Balustrade without the need to compromise with the product tested to perform.

- 10-12mm Glass
- Adjustable base plate
- Compatible with MOOD LED System

PAGE: 47





STRUT POSTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	SP10 Base Fix 2 point M10 fixing o substrate	Polish	SP10-PS	
	2205 duplex grade To be used with 10–13.52mm toughened or toughened laminated glass.	Brushed Satin	SP10-SS	
ID	No holes or cut outs required in glass.	Black	SP10-BK	
	SP15 Base Fix Heavy Duty Strut Post 2 point M12 fixing o substrate 2205 duplex grade	Polish	SP15-PS	
	For Occupancy A, B, C3, E and pool fences. Up to Very High Wind Zone. Can be used with 12–17.52mm toughened or toughened laminated glass.	Brushed Satin	SP15-SS	
110	No holes or cut outs required in glass. Engineered system. Strength exceeds round or square designs.	Black	SP15-BK	
	FIXING KITS	METRIC	CODE	PRICE

FIXING KITS	METRIC	CODE	PRICE
Masonry Fix	M10	SP10FK-1	
2x 115mm Threaded Rod, Flat Washer and Nut Stainless Steel	M12	SP15FK-1	
Steel Fix	M10	SP10FK-2	
2x 40mm Hex Bolt, Flat Washer and Nut Stainless Steel	M12	SP15FK-2	
Timber Fix	M10	SP10FK-3	
2x 180mm Coach Screw & HD Flat Washer Stainless Steel	M12	SP15FK-3	

STRUT POSTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	SP13 Face/Side Fix Heavy Duty Strut Post	Polish	SP13-PS	
	2 point M12 fixing o substrate 2205 duplex grade	U		
. J	For Occupancy A, B, C3, E and pool fences. Up to Very High Wind Zone.	1		
	Can be used with 12–17.52mm toughened or toughened laminated glass.	Brushed SP13-SS Satin		
	No holes or cut outs required in glass.	/A		
	Engineered system. Strength exceeds round or square designs.	Brushed Black	SP13-BK	

FIXING KITS	CODE	PRICE
Masonry Fix 2x 140mm M12 Threaded Rods, Flat Washers and Nuts Stainless Steel	SP13FK-1	
Steel Fix 2x 60mm M12 Hex Bolts, 4x Flat Washers and Nuts Stainless Steel	SP13FK-2	
Timber Fix 2x 140mm M12 Coach Screws & HD Flat Washers Stainless Steel	SP13FK-3	
Timber Through Fix 2x 180mm M12 Threaded Rods, 4x Flat Washers and Nuts Stainless Steel	SP13FK-4	

STRUT POSTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	SP14 Centrally Fixed Heavy Duty Strut Post	Polish	SP14-PS	
	Single or Double point M14/M12 fixing o substrate 2205 duplex grade			
•	For Occupancy A, B, C3, E and pool fences. Up to Very High Wind Zone.			
	Can be used with 12–17.52mm toughened or toughened laminated glass.	Brushed SP Satin	SP14-SS	
	No holes or cut outs required in glass.			
	Engineered system. Strength exceeds round or square designs.	Brushed Black	SP14-BK	
	(Includes center locking nut)			

FIXING KITS	CODE	PRICE
Masonry Fix 1 1x 180mm M14 Threaded Rod Stainless Steel	SP14FK-1	
Masonry Fix 2 2x 120mm M12 Threaded Rods Stainless Steel	SP14FK-2	
Steel Fix 2x 60mm M12 Threaded Rods, 2x Flat Washers and Nuts Stainless Steel	SP14FK-3	
Timber Through Fix 2x 180mm M12 Threaded Rod, 2x Flat Washers and Nuts Stainless Steel	SP14FK-4	

MINI POST SPIGOTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	PR160 Round Pool Spigot	Polish	PR160-PS	
	Domestic and Residential Occupancy A and C3. Rated to be used up to a High wind zone (1.76Kpa or less) To be used with 12mm Glass No Holes in Glass Required Pool & Balustrade	Satin	PR160-SS	
	Includes Baseplate for adjustment	Black	PR160-BK	

FIXING KITS & ACCESSORIES	CODE	PRICE
Masonry M10 Fix 4x 140mm M10 Threaded Rods, Flat Washers and Nuts Stainless Steel	PSFKIT-1	
Steel Fix 4x 60mm M10 Hex Bolts, 8x Flat Washers and Nuts Stainless Steel	PSFKIT-2	
Timber Fix 4x 140mm M10 Coach Screws & HD Flat Washers Stainless Steel	PSFKIT-3	
Timber Through Fix 4x 180mm M10 Threaded Rods, 8x Flat Washers and Nuts Stainless Steel	PSFKIT-4	

MINI POST SPIGOTS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
9	PS175 Square Pool Spigot	Polish	PS175-PS	
	Domestic and Residential Occupancy A and C3. Rated to be used up to a High wind zone (1.76Kpa or less) To be used with 12mm Glass No Holes in Glass Required Pool & Balustrade	Satin	PS175-SS	
	Includes Baseplate for adjustment	Black	PS175-BK	

FIXING KITS	CODE	PRICE
Masonry M10 Fix 4x 140mm M10 Threaded Rods, Flat Washers and Nuts Stainless Steel	PSFKIT-1	
Steel Fix 4x 60mm M10 Hex Bolts, 8x Flat Washers and Nuts Stainless Steel	PSFKIT-2	
Timber Fix 4x 140mm M10 Coach Screws & HD Flat Washers Stainless Steel	PSFKIT-3	
Timber Through Fix 4x 180mm M10 Threaded Rods, 8x Flat Washers and Nuts Stainless Steel	PSFKIT-4	

MFG POOL GATE LATCHES



POLARIS SOFT CLOSE HINGES

PRODUCT DESCRIPTION







POLARIS Soft Close Hinges 155 Series


The Polaris 155 Series RETROFIT HINGES were purposely designed to RETROFIT onto existing Spring Hinge gates. No need for costly new glass, quick and simple to install and available to suit almost every gate option. Featuring our "Quik-Adjust" Ratchet cap for simple speed adjustment and interchangeable dampers for complete customization closing force. Tested and NZ/AUS Pool compliance certified o 25,000 cycles.


Retrofi s directly into 8-12mm spring hinge glass gates (hole/cut out dependant)

Both self closing and soft closing f om any position

Quick and easy to install / D.I.Y


Quik-adjust ratchet cap for simple speed adjustment






PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	POLARIS Soft Close Glass to Glass Hinge	Satin Stainless	SC180-S	
	Retrofit able (various fixing options) Glass o Glass Soft Close g te hinge. 8-12mm Glass.	Polished Stainless	SC180-C	
	*SOLD AS A PAIR (2x Hinges)	Black	SC180-BK	
	POLARIS Soft Close Wall to Glass Hinge	Satin Stainless	SC090-S	
	Retrofit able (various fixing options) all to Glass So Close gate hinge. 8-12mm Glass. 45kg Max	Polished Stainless	SC090-C	
	*SOLD AS A PAIR (2x Hinges)	Black	SC090-BK	


EG GATE LATCHES





VIENNA HYDRAULIC GATE HINGES


PRODUCT	DESCRIPTION	TYPE	FINISH	CODE	PRICE (PR)
	EH4T Glass to Wall Hydraulic Hinge	NON-HOLD	Satin Stainless	EH4NHOSS	
	Hinge opening angle 100°. Self-closing from any angle. Available in non-hold open and hold open options. Centre T Style backplate.	OPEN	Polished Stainless	EH4NHOPS	
	Max recommended glass weight: 70kg Max recommended door span: 900mm Standard for 12mm glass, can be	HOLD	Satin Stainless	EH4HOSS	
	*SOLD AS A PAIR (2x Hinges)	OPEN	Polished Stainless	EH4HOPS	
	EH4L Glass to Wall Hydraulic Hinge	NON-HOLD	Satin Stainless	EH4NHOLSS	
	Hinge opening angle 100°. Self-closing from any angle. Available in non-hold open and hold open options. Offset L	OPEN	Polished Stainless	EH4NHOLPS	
0	Style backplate. Max recommended glass weight: 70kg Max recommended door span: 900mm Standard for 12mm glass, can be	HOLD	Satin Stainless	EH4HOLSS	
	*SOLD AS A PAIR (2x Hinges)	OPEN	Polished Stainless	EH4HOLPS	
	EH3 Glass to Glass Hydraulic Hinge	NON-HOLD	Satin Stainless	EH3NHOSS	
	Hinge opening angle 100°. Self-closing from any angle. Available in non-hold open and hold open options. Glass to	OPEN	Polished Stainless	EH3NHOPS	
	Glass Style. Max recommended glass weight: 70kg Max recommended door span: 900mm Standard for 12mm glass, can be	HOLD	Satin Stainless	EH3HOSS	
	supplied for 10mm *SOLD AS A PAIR (2x Hinges)	OPEN	Polished Stainless	EH3HOPS	













GATE PIVOT ARMS & PATCHES


PRODUCT	DESCRIPTION	TYPE	FINISH	CODE	PRICE
	PGA Patch to Patch Gate Pivot Arm		SSS	PGA-SS	
	Used with 2 MP20 Top Patch Fittings, Glass to Glass.		PSS	PGA-PS	
0	PWA Wall to Patch Ga	te Pivot Arm	SSS	PWA-SS	
	Suits Glass to MP20 Top Patch fi 10-12mm glass,	ttin	PSS	PWA-PS	
0 0 0	PGH2 Glass to Patch Gate Pivot Arm	44	SSS	PGH2-SS	
C	Suits Glass to MP20 Top Patch fittin 10-12mm glass,	620	PSS	PGH2-PS	
	PGH6 Glass to Patch 90 Gate Pivot Arm Suits Glass to MP20 Top Patch fittin 10-12mm glass,	<u></u>	SSS	PGH6-SS	
	HPT20/MP20		SSS	HPT20SS	
	Top Patch Fitting		PSS	HPT20PS	
	Suits 10-12mm glass, For Opus pi fittings. Adjus able pivot insert, F		Black	HPT20BLK	






GATE PIVOTS, CLOSERS & FLOOR SPRINGS

PRODUCT	DESCRIPTION	TYPE	FINISH	CODE	PRICE
HPT10 Bottom Patch Fitting			SSS	HPT10SS	
	Suits 10-12mm glass, For Opus floo spring	PSS	HPT10PS		
	HPT26 free swing pivot. Adjustable pivot insert, Factory set at 55mm		Black	HPT10BLK	





EFS840 Hydraulic Floor Spring Patch Kit

Double action floo spring including stainless steel cover plate. 2 spring strengths; 16Nm (weak), 25Nm (standard). Maximum door width 1100mm on standard spring and 800mm on weak spring.

Maximum door weight 100kg.

Non hold open version to be used only for Pool Gates. Suitable for use with Opus frameless patch fittings and ails.

Warranty 5years or 500,000 cycles.

16Nm (weak) SSS EFS840NHOW

25Nm (standard) SSS EFS840NHO



FH100 EN3 Closer Hydraulic Bottom Patch

Suits 8-12mm glass, Includes base pivot plate. Non hold open version only to be used for Pool Gates.


Applicable for door width of 750mm to 1000mm and weight up to 100kg.


5 year Warranty.

SSS EPCNHOSS

PSS EPCNHOPS

Black EPCNHOBLK





Base plate hole locations



S40/25 HANDRAIL FITTINGS

PRODUCT	DESCRIPTION	TYPE	CODE	PRICE
	S40 Squareline Interlinking Handrail Capping (5.8m) 5.8m stock lengths, 40mm wide x 30mm high, easy to install using simple tools, no on site welding required. Squareline is easily	Satin Stainless	\$40-\$\$	
	attached to the glass using a compression fi rubber molding. 2205 Duplex Suitable for 12-21.5mm glass Joiners, end caps and wall mount brackets are glued together using tube lock.	Polished Stainless	S40-PS	
30 <u>—</u> 40 — —	S25 Slimline Interlinking Handrail Capping (5.8m) 5.8m stock lengths, 25mm wide x 21mm high, easy to install using simple tools, no on site welding required. Squareline is easily	Satin Stainless	\$25-SS	
21 25 25	attached to the glass using a compression fi rubber molding. 2205 Duplex Suitable for 10-12mm glass Joiners, end caps and wall mount brackets are glued together using tube lock.	Polished Stainless	S25-PS	
	Straight Joiner	40mm	S40J-180	
		25mm	S25J-180	
	End Cap	40mm	S40-EC	
		25mm	S25-EC	
		40mm LH	S40-WAL	
	Wall Anchor	RH LH	S40-WAR S25-WAL	
		25mm RH	S25-WAR	
	Cast 90deg Corner	40mm	S40-J90	
	Cast 70deg Comer	25mm	S25-J90	
	Vertical Adjustable Joiner	40mm	S40-VAJ	
	vertical Adjustable Joiner	25mm	S25-VAJ	
	Horizontal Adjustable Joiner	40mm	S40-HAJ	
4	Horizofital Adjustable Joinel	25mm	S25-HAJ	
		SR2	5 / 12-13.5mm	
		SR4	O / 12-13.5mm	
	Link Rail Rubber Gasket	SR40	O / 12-15mm	
		SR40	D / 13-16mm	
		SR40	O / 16-19mm	
2580	Link Rail Loctite 243 50mlbottle	243	TL2680	

GLASS CLAMPS

PRODUCT	DESCRIPTION	CODE	PRICE
	Round Steel Glass Clamp - Flat Back No glass preparation required 35kg per clamp loading. 316 stainless steel (8mm, 10mm, 12mm)	GCF-1	
	Round Steel Glass Clamp - Round Back No glass preparation required Radius back to suit 50mm diameter post 35kg per clamp loading. 316 stainless steel (8mm, 10mm, 12mm)	GCR-1	
	Square Steel Glass Clamp - Flat Back No glass preparation required 35kg per clamp loading. 316 stainless steel (8mm, 10mm, 12mm)	SS200	
	Square Steel Glass Clamp - Round Back No glass preparation required Radius back to suit 50mm diameter post 35kg per clamp loading. 316 stainless steel (8mm, 10mm, 12mm)	SS201	
	Satin Stainless Steel Glass Clamp Adjustable to suit glass thickness. From 6mm to 10mm No Glass preparation required. 30kg per clamp loading. 316 Stainless steel	SS101	
	Security Pin Can be fit ed into SS200 x SS201 clamps	SP202	
	Radius Back Plate	RS102.50	
	To allow mounting of SS101 clamps to 50mm or 70mm diameter posts.	RS102.70	

BALUSTRADE STIFFENER BRACKETS

PRODUCT	DESCRIPTION	SIZE	CODE	PRICE
	H.D. Clamp 12 - 15mm	90° glass to wall. 65mm x 55mm x 25mm.	SBW-15	
9.5	Glass Stiffener b acket - No holes	90° glass to glass. 82mm x 55mm x 25mm.	SB90-15	
	Satin finish	180° glass to glass. 103mm overall x 25mm.	SB180-15	
	H.D. Clamp 17.5 - 21.5mm	90° glass to wall. 65mm x 55mm x 25mm.	SBW-21	
9.5	Glass Stiffener b acket - No holes required. Duplex 2205. Stainless Steel	90° glass to glass. 88mm x 55mm x 25mm.	SB90-21	
Satin finish		180° glass to glass. 103mm overall x 25mm.	SB180-21	

All brackets are supplied with a selection of gaskets to suit glass thickness and includes stainless steel clamping plates.

PANEL CLAMPS

PRODUCT	DESCRIPTION	FINISH	CODE	PRICE
	Balustrade Panel Clamp 180°	Polish	BC25-180-PS	
0	Will help align & stiffe 12-13.5mm Balustrade Panels	Satin	BC25-180-SS	
	No holes required 316SSS	Black	BC25-180-BK	
	Balustrade Panel Clamp 90°	Polish	BC25-90-PS	
0	Will help align & stiffe 12-13.5mm Balustrade Panels External screws. No holes required 316SSS	Satin	BC25-90-SS	
•		Black	BC25-90-BK	
	Balustrade Panel Clamp Wall Mount	Polish	BC25-WM-PS	
0 .	Will help align & stiffe 12-13.5mm Balustrade Panels	Satin	BC25-WM-SS	
•	External screws. No holes required 316SSS	Black	BC25-WM-BK	

HANDRAIL BRACKETS

PRODUCT	DESCRIPTION	DIMENSIONS	TYPE	CODE	PRICE	
20	Round Arm Section I Round Section Arm. Suitable for Timber or Stainle	10-15mm Glass	HBR90G			
	316 Satin Stainless Steel (SS) 10-15mm Glass (*Specify Glass thickness on	order)	Solid Wall Fixing	HBR90W		
L	Square Arm Section Square Section Arm. Suitable for Timber or Stainle		10-15mm Glass	HBS90G		
	316 Satin Stainless Steel (SS) 10-15mm Glass (*Specify Glass thickness on	order)	Solid Wall Fixing	HBS90W		
	Heavy Duty - Round Arm Section Bracket					
W.	Round Section Arm. Suitable for Stainless Steel H Requires a welded connection 316 Satin Stainless Steel (SS) 10-15mm Glass (*Specify Glass thickness on	andrails. on to the rail.	10-15mm Glass	HBHDR90G		
	Square Cover Kit		Satin Stainless	HB50SCK		

Additional HR50/R90 and S90 MFG brackets available on request P.OA.

HANDRAIL BRACKETS

PRODUCT	DESCRIPTION	DIMENSIONS	FINISH	CODE	PRICE
	HBGM1 Round Glass Mounted Handrail Bracket 2205 Duplex stainless steel, used with balustrades that require		Satin Stainless	HBGM1-SS	
	a load supporting interlinking rail 26mmØ hole in glass	3500	Polished Stainless	HBGM1-PS	
	HBGM2 Square Glass Mounted Handrail Bracket Made from 2205 Duplex	7. CO CO	Satin Stainless	HBGM2-SS	
	stainless steel, used with balustrades that require a load supporting interlinking rail 26mmØ hole in glass		Polished Stainless	HBGM2-PS	
	HBWM1 Round Wall Mounted Handrail Bracket Made from 2205 Duplex stainless steel. Mounted to the wall using 3x countersunk screws (screws not included)	75 Main Main Main Main Main Main Main Main	Satin Stainless	HBWM1-SS	
			Polished Stainless	HBWM1-PS	
	HBWM2 Square Wall Mounted Handrail Bracket Made from 2205 Duplex stainless steel. Mounted to the wall using 3x countersunk screws (screws not included)	Sondie 575	Satin Stainless	HBWM2-SS	
			Polished Stainless	HBWM2-PS	
	HBFS Handrail Bra	ncket Fixing Straddle	Satin Stainless	HBFS-SS	
	sections to the handrail br	Polished Stainless	HBFS-PS		



FREIGHT SERVICE & PRICING

	COURI	ER BAG	SMAL	L BOX	LARGE BO	X/LENGTH	>1.8-2.4M-	+ LENGTH	>2.4M+ l	ENGTH
SERVICE	NATIO	NWIDE	NORTH	SOUTH	NORTH	SOUTH	NORTH	SOUTH	NORTH	SOUTH
OVERNIGHT							N.A	N.A	N.A	N.A
2-3 Day Courier	N.A	N.A							N.A	N.A
2-5 Day Truck	N.A	N.A	N.A	N.A	N.A	N.A	N.A	N.A		
CARRIERS	comme	assistant.	coleman.	caleston i	alement.	a section is	aramex	aramex	D///	BASCIK

1-3 Day AKL Freight

FREIGHT FREE ON ALL ORDERS OVER \$1500+GST (excludes large & long balustrade/extrusion orders)

^{*}Pricing subject to change

^{*}Pricing & Lead Times indicative only, Please get in touch with customer services for an POA Freight Quote if needed.

^{*}Opus cannot guarantee the delivery turnaround service due to unpredictable possibilities and delays that can affect carriers lead times.

^{*}Oversized Deliveries & Shipments such as Balustrades POA.

OPUS HARDWARE | SERVICE OFFERING

			-
SERVICE	NORTH	SOUTH	DELIVERY
Standard Stock Items	1-3	2 - 4	Working days (Standard Delivery) from order placement.
Oversized Items	2 - 4	4 - 6	Working days (Standard Delivery) from order. (Greater than 2.5m in length, or overweight)
Powdercoated Items	7 - 10	10 - 15	Working days (Standard Delivery) from order placement.
Anodised Items	20 - 25	25 - 30	Working days (Standard Delivery) from order placement.
Site Speci c PS1's	10 -	- 15	Working days (Standard Duration) from order placement.
Custom or Speci c Engineering	Tr	20	At time of order placement with
International Orders	16	3C	Customer Service Department.







^{*}Opus cannot guarantee the delivery turnaround service due to unpredictable possibilities and delays that can affect carriers lead times. Lead Times indicative only.

POWDERCOATING PRICELIST

DESCRIPTION	CODE & PRODUCT	PRICE	PROI	DUCT
Standoffs, Disc Sets PER DISC	PC1-DISC			
Spigots, Mini Posts PER POST	PC1-SPIGOT		1	
Gate Hinges, Latches PER HINGE, LATCH	PC-HINGE			
Brackets, Clamps PER BRACKET	PC-BRACKET			
Covers, Channels, Extrusions & Handrails PER M OF EXTRUSION	PC-PERM			

^{*}Pricing subject to change

^{*}Minimum spend \$150+GST per order

^{*}Pricing based on standard Powdercoat Range, special powders may incur surcharge

^{*}Project rates or larger qty jobs P.O.A.



