



1000 - 2000
REFER OCCUPANCY
GUIDE PAGE 82 OF
THE OPUS TECHNICAL
MANUAL DRAWING
OB 100/24

OPUS ORDER FORM FOR FACE FIX CONCRETE	
CUSTOMER NAME:	
CUSTOMER ORDER NUMBER:	
NUMBER OF POSTS REQUIRED:	
THICKNESS OF GLASS BEING USED REFER OPUS DRAWING OB100/5 FOR OCCUPANCY TYPE.	10-12-15-16
HEIGHT FROM FLOOR TO TOP OF GLASS REFER OPUS DRAWING OB101/5 FOR OCCUPANCY TYPE - (SEE A ON DRAWING)	MM
STAINLESS STEEL TOP CAP FINISH - MIRROR POLISH	YES/NO
STAINLESS STEEL TOP CAP FINISH - SATIN (BRUSHED)	YES/NO
STAINLESS STEEL TOP CAP FINISH POWDERCOATED TO MATCH POST	YES/NO
POWDERCOAT FINISH.	YES/NO
COLOUR REQUIRED:	
FIX KIT #3 REQUIRED:	YES/NO
CONTENTS OF OPTIONAL FIXING KIT #3 STAINLESS STEEL M12 DOME NUTS - 2NO STAINLESS STEEL SPRING WASHERS M12 - 2NO STAINLESS STEEL FLAT WASHER M12 X 24MM - 2NO NYLON TOP HAT INSERTS M12 X 24MM - 2NO NYLON TOP HAT INSERTS M12 X 32MM - 2NO STAINLESS STEEL WASHERS M12 50MM X 50MM - 2NO STAINLESS STEEL STUD M12 X 205MM - 2NO	

© OPUS MANUFACTURING LTD 2012

FIXING CENTRES CAN BE REDUCED
TO 100MM ON RESIDENTIAL
INSTALLATION ONLY.

THIS POST IS PROTECTED BY NZ DESIGN APPLICATION NO 416723

DRAWING UPDATED 31/05/19 TO SHOW MAX 2MTR HEIGHT

OPUS™ MANUFACTURING LTD.
11 Grasslands Place
P.O.Box 5750 Frankton, Hamilton, New Zealand
Telephone: +64 7 847 5001
Fax: +64 7 847 5003

**ORDER FORM FOR OPUS MANUFACTURING
FACE FIX BALUSTRADE SYSTEM OB101
FOR INSTALLATION ON CONCRETE**

OPUS PART NUMBER OB101

DRAWING NUMBER: OB101/9