



OPUS ORDER FORM FOR TOP FIX TIMBER/STEEL	
CUSTOMER NAME:	
CUSTOMER ORDER NUMBER:	
NUMBER OF POSTS REQUIRED:	
THICKNESS OF GLASS BEING USED REFER OPUS DRAWING OB100/3 FOR OCCUPANCY TYPE.	10-12-15-16
HEIGHT FROM FLOOR TO TOP OF GLASS REFER OPUS DRAWING OB100/3 FOR OCCUPANCY TYPE - (SEE A ON DWG)	MM
STAINLESS STEEL TOP CAP FINISH - MIRROR POLISH	YES/NO
STAINLESS STEEL TOP CAP FINISH - SATIN (BRUSHED)	YES/NO
STAINLESS STEEL TOP CAP FINISH POWDERCOATED TO MATCH POST	YES/NO
POWDERCOAT FINISH.	YES/NO
COLOUR REQUIRED:	
FIX KIT #2 REQUIRED:	YES/NO
CONTENTS OF OPTIONAL FIXING KIT #2	
STAINLESS STEEL M12 DOME NUTS - 4NO	
STAINLESS STEEL SPRING WASHERS M12 - 4NO	
STAINLESS STEEL FLAT WASHER M12 X 24MM - 4NO	
STAINLESS STEEL WASHERS M12 50MM X 50MM - 4NO	
STAINLESS STEEL M12 NUTS X 4NO	
NYLON TOP HAT INSERTS M12 X 24 - 4NO	
STAINLESS STEEL STUD M12 X 300MM - 4NO - (B ON DRAWING)	

© OPUS MANUFACTURING LTD 2012

THIS POST IS PROTECTED BY NZ DESIGN APPLICATION NO 416723

DRAWING UPDATED 31/05/19 TO SHOW MAX 2MTR HEIGHT

OPUS™ MANUFACTURING LTD.
 11 Grasslands Place
 P.O.Box 5750 Frankton, Hamilton, New Zealand
 Telephone: +64 7 847 5001
 Fax: +64 7 847 5003

**ORDER FORM FOR OPUS MANUFACTURING
 TOP FIX BALUSTRADE SYSTEM OB100
 FOR INSTALLATION ON TIMBER/STEEL**

OPUS PART NUMBER OB100

DRAWING NUMBER: OB100/8